



US 20030095612A1

(19) **United States**(12) **Patent Application Publication** (10) Pub. No.: **US 2003/0095612 A1**
Glas et al. (43) Pub. Date: **May 22, 2003**(54) **SYSTEM AND METHOD FOR AN
IF-SAMPLING TRANSCEIVER**

(52) U.S. Cl. 375/329; 375/355

(76) Inventors: **Jack P. Glas**, Basking Ridge, NJ (US);
Vladimir I. Prodanov, New
Providence, NJ (US)(57) **ABSTRACT**

Correspondence Address:
GARDNER GROFF, P.C.
PAPER MILL VILLAGE, BUILDING 23
600 VILLAGE TRACE
SUITE 300
MARIETTA, GA 30067 (US)

The present invention is directed toward a radio, and method for receiving radio frequency signals. The radio comprises an input signal at a first intermediate frequency, an intermediate sampling architecture, a quantizer and a baseband converter. The intermediate frequency sampling architecture comprises receiving the input signal, passing the first intermediate frequency signal through a first filter characterized by steep selectivity and narrow bandpass, converting the filtered signal to a second intermediate frequency and passing the second intermediate frequency signal through a second filter having a bandpass characteristic, but without the steep selectivity characterizing the first filter. The radio further comprises a third filter following the baseband conversion which filters out adjacent channel harmonics to obtain a wanted data signal.

(21) Appl. No.: 09/989,605

(22) Filed: Nov. 20, 2001

Publication Classification(51) Int. Cl.⁷ **H04L 27/22; H04L 7/00;**
H03D 3/22